



190 / 290 / 390				
Ø-DN	15	20	25	32
A	88	100	120	149
C	30	35	40	45
H	28	35	39	43
O	1/2"	3/4"	1"	1"1/4
Kg	0,4	0,6	1	1,6

190 / 290 / 390. Ø. Ø				
Ø-DN	15/20	20/25	25/32	32/40
A	88	100	120	149
C	44	53	59	64
H	28	35	39	43
O	3/4"	1"	1"1/4	1"1/2
Kg	0,46	0,7	1,2	1,75

CONCEPTION

Bronze -CuSn5ZnPb / ASTM B62

Clapet FPM	Réf : 190	-15 + 200°C
Clapet PTFE	Réf : 390	-196 + 225°C
Clapet Métal	Réf : 290	-196 + 225°C
Clapet Silicone	Réf : 190BP	-15 + 200°C

Entrée Mâle / Sortie Femelle

Dispositif de relevage

Orifices décalés 190 / 290 / 390.Ø.Ø

APPLICATIONS

Eau chaude & Fluides Industriels

Fluides aqueux

Vapeur basse pression (8 Bar)

Gaz neutres (air comprimé,...)

OPTIONS

Nickelage / Chromage

Clapet dégraissé



PMS/MSP 40 Bar

FPM Disc	Ref : 190	-15 + 200°C
PTFE Disc	Ref : 390	-196 + 225°C
Metal Disc	Ref : 290	-196 + 225°C
Silicone Disc	Ref : 190BP	-15 + 200°C

Male inlet / Female outlet

With lifting test handlever

Different size in outlet 190 / 290 / 390.Ø.Ø

Hot water & Industrial fluids

Water-based fluids

Low pressure steam (8 Bar)

Neutral gases (air compressed, ...)

Nickel / Chrome plating

Degreased disc / seat