



182 / 282				
Ø-DN	15	20	25	32
A	100	114	136	167
C	30	35	40	45
E	40	49	55	61
O	1/2"	3/4"	1"	1"1/4
Kg	0,38	0,73	1,35	1,71

182 / 282 Ø.Ø				
Ø-DN	15/20	20/25	25/32	32/40
A	100	114	136	167
C	44	53	59	64
E	40	49	55	61
O	3/4"	1"	1"1/4	1"1/2
Kg	0,42	0,76	1,45	1,85

CONCEPTION

Bronze -CuSn5ZnPb / ASTM B62

Clapet FPM

Réf 182 -15 + 200°C

Clapet PTFE

Réf 282 -196 + 225°C

Calpet Silicone

Réf 182BP -15 + 200°C

Entrée / Sortie Femelle

Emcombrement limité / Avec système de relevage

Ressort isolé du fluide

Orifices décalés

PMS/MSP 40 Bar

FPM Disc

Ref 182 -15 + 200°C

PTFE Disc

Ref 282 -196 + 225°C

Silicone Disc

Ref 182BP -15 + 200°C

Female Inlet / Outlet

Reduced housing / With handlever

Spring protected from fluid

Different size in outlet

APPLICATIONS

Eau chaude & Fluides Industriels

Fluides aqueux

Vapeur basse pression (8 Bar)

Gaz neutres (air comprimé,...)

Hot water & Industrial fluids

Water-based fluids

Low pressure steam (8 Bar)

Neutral gases (air compressed,...)

OPTIONS

Nickelage / Chromage

Connexion à brides ou NPT

Clapet dégraissé



Nickel / Chrome plating

Flange or NPT connection

Degreased disc / seat